



KENNDATENBLATT / TECHNICAL DATA SHEET

Desorex G 50

Cylindrically shaped activated carbon / impregnated

®Desorex G 50 is an alkaline impregnated carbon based on coal, which can be used for the removal of hydrogen sulfide from natural gas, bio gas or sewage gas.

Hydrogen sulfide is chemically bounded and fixed in the complex pore system of the activated carbon.

®Desorex G 50 has a high adsorption capacity for organic substances.

Specifications:

Impregnation (wt.%)	approx. 5
Bulk density (kg/m ³)	570 ± 10%
Moisture content (wt.%) (as packed)	< 15
Diameter of particles (mm)	approx. 4

Product data before impregnation:

Total surface area (m ² /g) (BET-method)	950
CTC-adsorption (wt.%)	> 50
Hardness (wt.%)	approx. 95

Remarks:

The above data are based on analyses of the activated carbon and test methods according ASTM and Donau Carbon. Copies are available on request.

The activated carbon is irritant. Avoid contact with skin and eyes; in case of need rinse with water and consult a physician.

e1802/02

Donau Carbon GmbH
Gwinnerstr. 27-33
60388 Frankfurt am Main, Germany
Tel.: +49-(0)69-4011-426
Fax: +49-(0)69-4011-659
Email: office@donau-carbon.com

Donau Carbon US LLC
551 N. US Highway 41
Dunnellon, FL 34432, USA
Tel.: +1-352-465-5959
Fax: +1-352-465-0679
Email: sales.us@donau-carbon.com



**Unser QM-System ist zertifiziert
Our QM-system is certified**